

ABOX-5100G

AMD Ryzen™ Embedded V1000 Processor w/
8 x GbE/ 2 x COM/ 4 x DP/ 4 x HDMI/
4 USB 3.0/ AMD Radeon™ E9260 GPU/
9-48V Input AI GPU Computing

Features

- AMD Ryzen™ Embedded V1000 Platform
- AMD Embedded Radeon™ E9260 GPU
- 8 x GPI, 4 x GPO and 2 x RS-232/422/485
- Dual Hot Swappable SATA Storage
- 9-48V DC Input and Operating Temp.: -40~60°C
- 8 x GbE LAN (Optional for 8 x PoE)



Taiwan Patent No. M447854

Taiwan Patent No. M565941
for thermal cooling



Delay Time



Power Ignition



Wide Range



Wireless



Battery Backup

System	
CPU	AMD Ryzen™ V1807B Quad Core Soc (3.3~3.6GHZ)
Memory	2 x DDR4 2400 MHz SO-DIMM up to 32GB
LAN Chipset	Intel i210
Watchdog	1 ~ 255 Level Reset
TPM	2.0
I/O	
Serial Port	3 x RS 232/422/485
USB Port	4 x USB 3.0 Ports
LAN	8 x RJ45 Ports for GbE (Optional for 8 x PoE total 100W max.)
Video Port	4 x DP, 4 x HDMI
DIO Port	8 x GPI and 4 x GPO
Audio	1 x Line-out, 1 x Line-in and 1 x Mic-in
Expansion Bus	3 x Full Mini-PCle Slots and 1x M.2 A-E Key 2230 slot (2 x SIM Card Sockets for 3G/LTE)
Graphics	
Graphics	AMD Radeon™ E9260 GPU Support for OpenGL 4.5. and OpenCL™ 2.0. Support for Mantle and AMD LiquidVR™ Support for DirectX® 12 (Feature Level 12_0) features
Resolution	Max Resolution (HDMI 2.0b) : 5120x2880@60Hz
Power Requirement	
Power Input	9V - 48V DC Power Input
Power Protection	Automatics Recovery Short Circuit Protection
Power Management	Vehicle Power Ignition for Variety Vehicle
Power Off Control	Power off Delay Time Setting by BIOS and Software
Battery(UPS)	Internal Battery Kit for UPS (Optional) Patent No. : M447854 - Build-in Battery

Storage	
Type	2 x 2.5" Drive Bay for SATA Type HDD/SSD
Environmental	
Operating Temp.	-40°C ~ 60°C * CPU configure at 25W, ambient w/ 0.6m/s airflow
Storage Temp.	-40°C ~ 80°C
Relative Humidity	0% RH ~ 95% RH
Vibration (random)	IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD
Vibration Operating	MIL-STD-810G, Method 514.6, Procedure I, Category 4
Shock	Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Certifications	CE, FCC Class A, E13
Mechanical	
Construction	Aluminum Alloy
Mounting	Wall-mount
Weight	5220g (Barebone)
Dimensions	260(L) x 226(W) x 95(H) mm
Ordering Information	
Part Number	ABOX-5100G-V1807 ABOX-5100 PG1-V1807 (with PoE)
Description	AMD Ryzen™ Embedded V1000 Processor w/ 8 x GbE/ 2 x COM/ 4 x DP/ 4 x HDMI/4 USB 3.0/ AMD Radeon™ E9260 GPU/ 9-48V Input AI GPU Computing
State of Origin	Made in Taiwan